

MiniMavis

Portable Remote Surveillance and Video Transmission System



Features

- Small, Lightweight and Rugged
- Portable Tripod Mounted Camera
- Up to 5km Range
- 12v Battery Operated
- Day/Night Camera
- Up to 25:1 Optical Zoom with x12 Digital
- Wired or Wireless Link (Analogue or COFDM)
- Thermal Imaging Option
- Low Power Consumption

Description

Utilising the popular 2712CM series camera and 2720 Intelligent Pan & Tilt, MiniMavis is a remote control camera system, which can be deployed quickly and monitored at a distance of up to 5km using the Britannia 2000 Ltd TeleCase and optional microwave wireless link.

Applications

The system is ideal for covert operations and where the speed of deployment is crucial, such as fire-fighting surveillance and fly-tipping.

Options

- Colour
- Resets
- Analogue or COFDM microwave links

Accessories

- TeleCase
- Tripod
- Solar panel
- Lights (white or IR)
- Long life battery

Specifications

Choice of Cameras

Sensor:	1/4" Exview™ HAD CCD	1/6 Super HAD™ CCD
Pixels:	752 (h) x 582 (v) (PAL)	752 (h) x 582 (v) (PAL)
Resolution:	460 TV lines (PAL)	460 TV lines (PAL)
Sensitivity:	Colour: 0.7 lux, Mono: 0.1 lux	Colour: 3.0 lux, Mono: 0.5 lux
Zoom:	18x optical & 12x digital (216x total)	25x optical & 12x digital (300x total)
System:	PAL or NTSC	PAL or NTSC
Output:	PAL 1v p-p, (YC optional)	PAL 1v p-p, (YC optional)
Angle of View (H):	48° (wide) to 2.7° (Tele)	45° (wide) to 2° (Tele)
F Stop:	F1.4 to F3.0 at max zoom	F1.6 to 2.7 at max zoom
Focus:	Auto with manual over-ride	Auto with manual over-ride